
# HOMELITE®

# 1050 AUTOMATIC Chain Saw



# **SPECIFICATIONS**

## **ENGINE**

 LONGER ENGINE LIFE—Heavy duty chromeplated cylinder with extra cooling fins

- TYPE Homelite, single cylinder, 2 cycle (loop scavenged).
- DRY WEIGHT 21 pounds.
- **DISPLACEMENT** 6.1 cubic inch.
  - BORE 2%6".
  - STROKE 1%".
- ENGINE SPEED 6000 RPM, under load.
  - **BEARINGS** Heavy duty ball and antifriction needle.
  - **STARTER** Pawl type, positive engagement with automatic rewind.
  - MUFFLER Spark arresting, baffled, quiet type.
  - CLUTCH Heavy duty centrifugal, 2800 RPM engaging speed.

#### **FUEL SYSTEM**

- CARBURETOR
  Tillotson, all position, double diaphragm with integral fuel pump, accelerator pump, and fuel strainer, external adjustments.
- INTAKE VALVE Pyramid, with 4 stainless steel reeds.

  FUEL CAPACITY 49 oz.
- FUEL PICK-UP Flexible fuel pick-up with replaceable filter.
- AIR FILTER Micro mesh fiber with integral gasket.

  THROTTLE CONTROL Trigger in handle with safety starting
  - FUEL MIXTURE with each gallon of regular gas mix ½ pint (16:1) Homelite oil or SAE 30 oil.

## **IGNITION SYSTEM**

- MAGNETO High tension, moisture and dust proof.
- BREAKER POINT O.015," protected in sealed box under flywheel.
  - TIMING 30° BTDC static.
- SPARK PLUG Champion CJ-6, .025" gap.

### **GUIDE BAR, CHAIN AND SPROCKET**

- GUIDE BAR 

  .063" gauge, induction hardened with welded hard-faced tip, sizes 17" to
  - CHAIN .404" pitch #59 Oregon micro-bit.
- CHAIN SPEED 3200 feet per minute.
- CHAIN OILER
  TYPE

  Positive, crankshaft driven, automatic plus separate manual pump.
- CHAIN OILER 8 Oz. reservoir.
  - SPROCKET 8 tooth, .404" pitch.

#### GENERAL

- HANDLE BARS Vinyl coated flush cut or optional wrap-around.
- ATTACHMENTS 

  Plunge-cut bow, clearing and utility bars.
- BUMPER SPIKE Standard or optional extra long.

HOMELITE®

A (extron)
DIVISION
PORT CHESTER, N.Y. U.S.A.

TB-428AB

6123GJ

552 Specifications Subject to Change without Notice.

DEALER