

HOMELITE MODEL 410 CHAIN SAW

FEATURES

ENGINE

Dry Weight: 15 lbs. 8 oz.

Displacement: 4.1 cu. in. (67.2cc)

Bore: 1.94" (49.2mm)
Stroke: 1.38" (34.8mm)
Speed: 9000 RPM (cutting),
2500-3000 RPM (idle)

Bearings: Ball bearings on crank shaft: Silver plated

caged roller crankpin bearing, Needle wrist pin

bearing

Clutch: Three piece, lined clutch, inboard sprocket

Muffler: Softone® dual chamber, USFS Approved, Front

mounted, bottom exit

IGNITION

Magneto: High voltage capacitor discharge Timing: Automatic retard and advance

Spark Plug: Champion DJ-7Y Spark Plug Gap: .025"

CARBURETION AND FUEL

Carburetor Type: Diaphragm

Intake Valve: Pyramid type and reed valve

Air Filter: Micro-mesh, cartridge type Fuel Capacity: 24 fl. oz. (.71)

Throttle Control: Trigger in the rear handle, safety in-

terlock throttle latch for starting

CHAIN AND GUIDE BAR

Guide Bar. 16-31" Power Tip, Gas Welded or Sprocket

Nose Bars

Chain: Homelite #38 Series, 3/8" pitch

Chain Speed: 3940 ft. per minute at 9000 RPM

Sprocket: Star type 7 tooth, 3/8" pitch; Optional-rim

sprocket

Chain Oiling System: Positive displacement crankshaft

driven automatic pump with manual

override

Chain Oil Capacity: 12 fl. oz. (.35l)

GENERAL

Safe-T-Tip®: Anti-kickback device

Hand Guards: Standard

Noise Level: 100 DBA at operator's ear at 7000 RPM

83 DBA at 50 ft. at 7000 RPM

Vibration: 3-4g's at 7000 RPM Chain Brake: Optional

BENEFITS

Light but rugged

Powerful enough for 16" to 31" guide bar

High engine speed for fast cutting

Long life engine components Heavy duty, long life, low slip

Quiet operation

No breaker points and long plug life

Makes starting easy

All position operation

Optimum power at all engine speeds and good low speed

orque

Increased filter area for less frequent cleaning Operates up to 35 minutes without refueling

All controls within easy reach of fingers and hands

Heavy duty bars for all applications

Excellent all around saw chain

High chain speed for fast, smooth cutting

Assures proper chain speed for all around sawing

Allows customized oil flow to match cutting demands
Ample oil for continuous lubrication with each tank of fuel

Eliminates kickback

Saw fitted with left and right hand guards

Quiet operation

Smooth running

HOMELITE TEXTRON

Homelite Division of Textron Inc