
MODEL 900G

An improved model of the 9-26 three-gear chain saw released in April, 1960.

GEAR RATIOS: 2.84:1 and 3.57:1.

COLOR SCHEME: Black pistol grip; Red cylinder shield, cylinder shroud, air shroud; Canyon Green crankcase, gearcase, and fuel tank.



- 1. Name Plate: Model No. 900G Serial No.____
- 2. Shortened cylinder shroud and other modifications not reliable in identifying Model 900 units as these new designs may have been added to earlier models in the field.
- 3. Decals: 900G on pulley cover, cylinder shroud and gearcase cover.

UNIT SPECIFICATIONS

* MODEL 900GA Integral Crankcase-Drivecase **BASIC STYLE Bottom Mounted Tank TRANSMISSION** Туре Three Gears 2.84:1 standard 3.57:1 optional Ratio %6"-7 Sprocket Pitch/No. of Teeth Integral with fuel tank Chain Oil Reservoir Reservoir Capacity 13 ounces STARTER TYPE Homelite Ball Drive Rotation (from starter side) Counterclockwise **ENGINE** 25/6" Bore 15/8" Stroke Displacement-cu. in. 6.83 Main Bearing I.D. .7870/.7874 Seal - Magneto Side Garter-type Garlock Garter-type Garlock and Vellumoid Gasket Seal - Main Bearing Piston Rings - Height 1/6" Width .097/.107 **End Gap** .070" min.-.080" max. Governor Type * Peak horsepower at 6000 RPM **IGNITION SYSTEM** Spark Plug HO-3 Spark Plug Gap .025" Type Magneto Phelon **Breaker Point Setting** .015" Primary Coil Resistance .65-.80 ohms Secondary Coil Resistance 7500-9500 ohms .18-.22 mfds. Condenser Capacity **FUEL INDUCTION** SYSTEM Tank Construction **Bottom Mounted Fuel Capacity** 56 ounces Fuel Feed Carb. Diaphragm Pump Type Carburetor Diaphragm Model Tillotson HL-62A or HL-62AX Wix Pleated Paper Fiberglas optional Air Filter Type Intake Valve Pyramid Reed

^{*}These models now supplied without governor. Earlier models have Air-Vane governor.