


Convertible to Gear Drive in Minutes . . .



DIRECT DRIVE

CHAIN SPEED (under load) 7 Tooth .404" pitch

sprocket 2828 ft./min.



GEAR DRIVE

GEAR RATIO

1:2.9

CHAIN SPEED (under load)

7 Tooth 1/2" pitch.

sprocket 1208 ft./min.

3 Tooth ,404" pitch

sprocket 1115 ft./min.

Available with:

8 Tooth .404" pitch sprocket

7 Tooth 1/2" pitch sprocket

HOMELITE SPECIFICATIONS

C-71

ENGINE



ENGINE TYPE — HOMELITE two cycle, loop scavenged single cylinder

BORE -2"

STROKE - 1%"

DISPLACEMENT — 4.91 cubic inch

INTAKE VALVE - Flat Reed

COMPRESSION RATIO — 6.7:1

IGNITION TIMING — 30° BTDC Static

ENGINE SPEED — Under load — 6000 - 6500 RPM

CLUTCH ENGAGING SPEED AND TYPE

— 2800 RPM — 6 shoe double spring centrifugal

BREAKER POINT SETTING AND LOCA-TION — .015" — protected in sealed box under flywheel

SPARK PLUG TYPE AND GAP — Champion J-6-J — .025"

THROTTLE CONTROL — Trigger in handle with throttle lock


BEARINGS — Needle and Ball Bearings

CHAIN TYPE — .404 Pitch #52 OMark Chipper

SPROCKET - 7 Tooth, .404 Pitch

CHAIN SPEED UNDER LOAD — 2828 Feet per Minute

FEATURES



CARBURETOR — Tillotson All-Position
Diaphragm with integral fuel
pump and fuel strainer . . . external high, low, idle speed adjustments

STARTER — Homelite Recoil Positive Engagement with Replaceable Starter Rope Bushing

MAGNETO — High tension — water and dust proof with protected coil


FUEL FILTER — All-Position Felt Pickup in fuel tank, wire mesh screen in carburetor

AIR FILTER — Protected Micro Mesh
Polyester Fiber for long service
life

MUFFLER — Quiet Type — with baffled spark arrestor

CHAIN OILER TYPE AND CAPACITY—
Positive Manual 8 oz. reservoir
w/filter

DATA



WEIGHT LESS BAR AND CHAIN — 181/2 lbs.

FUEL TANK CAPACITY — 42 oz. with pressure sensitive replaceable automatic vent

FUEL TYPE AND MIXTURE — Regular gasoline mixed with HOMELITE OIL or SAE 30 motor oil 16:1 (1/2 pint per gallon)

BAR SIZES — 14, 17, 21, 25,

ATTACHMENTS — Bow, Clearing, and Utility Guides

HANDLE BAR TYPES — Flush cut, or wrap-around plastic grip

HOMELITE

A TEXTON DIVISION PORT CHESTER, N.Y. U.S.A.

MANUFACTURERS OF GASOLINE-ENGINE-DRIVEN PUMPS, GENERATORS, RIDE-ON LAWN MOWERS, OUTBOARDS, CHAIN SAWS, AND CIRCULAR SAWS