


HOMELITE®

SUPER WIZ 55 CHAIN SAW



SUPER WIZ 55 SPECIFICATIONS

ENGINE

Type: Homelite, single cylinder 2 cycle (loop scavenged).

Dry Weight: 21.5 pounds (9.77 Kg.) less bar and chain.

Displacement: 4.3 cubic inch (70.8 cc).

Bore: 2 inches (50.8 mm).

Stroke: 1.38 inches (35 mm).

Speed: 6000-6500 RPM, under load; 7500-8000 RPM, no load.

Bearings: Heavy duty ball, and antifriction needles.

Starting: Positive engagement with automatic rewind.

Clutch: Heavy duty, 6 shoe, double spring centrifugal, automatically engages at 2700 RPM.

IGNITION

Magneto: High tension with epoxy impregnated coil. Moisture, dust and temperature resistant.

Timing: 34° BTDC static.

Breaker Point: .015 inch.

Spark Plug: Champion J6J or UJ11G, .025 inch gap.

CARBURETION AND FUEL

Carburetor Type: Tillotson all-position diaphragm type with integral fuel pump and strainer.

Intake Valve: High performance pyramid-reed.

Air Filter: Protected micro-mesh fiber for long service life.

Fuel Capacity: 43.4 oz. (1.28L) fuel tank has replaceable automatic vent.

Fuel Pick-Up & Filter: Flexible fuel pick-up with replaceable filter.

Fuel Oil Mixture: With each gallon of regular gas, mix 1/2 pint Homelite 2-cycle engine oil or SAE oil (16:1 ratio).

Throttle Control: Trigger in handle with trigger latch for starting ease.

CHAIN AND GUIDE BAR

Guide Bars: 19", 23", 27", 32", 44", 50", 60".

Chain: 1/2" pitch Homelite #50 series.

Sprocket: 8 tooth, 1/2" pitch, spur type.

Chain Oiling Systems: Operator controlled positive plunger pump 5.3 oz. (.16L) reservoir with filter.

GENERAL

Handle Bars: Flush cut or wrap-around.

Bumper Spike: Included.

Attachments: Bow & clearing guides.

Gear Box: 3.57 to 1.

Gear Lubricant: Homelite SAE 90 gear oil.

HOMELITE®

Extron

DIVISION

PORT CHESTER, NEW YORK, U.S.A. 10573