## HOMELITE

DIRECT DRIVE CHAIN SAW



## HOMELITE

A DIVISION OF TEXTRON INC.
PORT CHESTER, NEW YORK, U.S.A.

## MECHANICAL FEATURES OF THE NEW 707D CHAIN SAW

- 1. New, heavier, counterbalanced crankshaft has been increased in diameter ½6" on magneto end, ¾2" on the crankpin and ½8" on reinforcing boss on magneto side.
- 2. New longer stroke increases displacement to 5.8 cu. in. adding about 6% more power.
- 3. New, flat, pleated, strong, paper air filter with 70 square inches of filtering area.
- 4. The new filter, recessed in rear of tank, scoops air in from back of saw Easily removed for quick cleaning. Stays cleaner longer.
- 5. New switch located close to throttle for easier control of unit.
- 6. New fitted bolts in drive case provide more rugged mounting for guide bars regardless of length.
- 7. New third point mounting for handle bar, in bottom recess of air shroud, gives solid support for heavy duty production cutting.
- 8. 6" diameter magneto rotor provides extra cooling for more powerful engine.
- 9. New connecting rod with bigger needle bearing for greater load carrying capacity.
- 10. Automatic governor keeps engine at proper speed range and avoids overheating of engine.
- 11. New, improved magneto with attached breakerarm pivot post for easy assembly and disassembly.

## GENERAL SPECIFICATIONS ON THE 707D CHAIN SAW

Type Sprocket . . . . . .  $\frac{7}{16}$  Pitch, 7 Tooth

Chain Speed f.p.m. . . . . No Load 3573, Load 3062

Weight . . . . . . . Dry-less bar, chain, 19 lbs., 3 oz.



A DIVISION OF TEXTRON INC

PORT CHESTER, NEW YORK