


HOMELITE®

XL-88 MULTI-PURPOSE SAW

**A new Demolition Saw for
Contractors, Builders,
Demolition Crews.
Cuts Masonry, Pavement,
Wood, Metal or any
Composite Material.**




• Heavy Duty Guard

• Dual Spindle
Allows Full
Depth, Flush Or
Normal Cutting.

• Solid State Ignition
(No Breaker Points)

XL-88

• Famous XL Engine





HOMELITE

SPECIFICATIONS

FEATURES



- SAFETY STANDARDS** ● Conforms to ASA and National Safety Council standards where applicable.
- WHEEL DIAMETER** ● 12" Carbide-tipped Blade or Abrasive Wheel (Abrasive wheels must be reinforced).
- WHEEL LOCATION** ● Cutter and Guard can be installed on either side of arm for outside cutting in limited space or center cutting for best balance.
- WHEEL DRIVE** ● Rugged Polyflex* non-stretch belt. Arbor mounted in ball bearings.
- APPROXIMATE SPEED** ● Engine no load speed 6000 RPM. Wheel no load speed 5000 RPM (15,700 S.F.M.). Clutch engages at 3000 RPM engine speed.
- GOVERNOR** ● Air vane governor limits top speed for safety.
- SPEED CONTROL** ● Throttle trigger in handle for convenience.

ENGINE

- MAKE AND MODEL** ● Homelite XL type.
- TYPE** ● Single cylinder, air-cooled, loop scavenged, two cycle gasoline engine.
- DISPLACEMENT** ● 5.0 cubic inches.
- BORE** ● 2 1/8 inch diameter.
- STROKE** ● 1 1/2 inch.
- IGNITION** ● High tension, flywheel type magneto with Solid State circuit. No breaker points to pit, corrode or change adjustment or fill with dust. No change in spark timing or ignition voltage with age.
- LUBRICATION** ● Fuel-Oil mixture — 1/2 pint Homelite or SAE 30 motor oil per gallon of regular gasoline (16 to 1).
- FUEL CAPACITY** ● 2 3/4 pints.
- AIR CLEANER** ● Special double element micro-mesh fibre with integral molded gasket.
- CARBURETOR** ● Tillotson all-position, double diaphragm type with integral fuel pump and strainer. Has high speed and idle mixture adjustments.
- INTAKE VALVE** ● Pyramid with four stainless steel reeds. No adjustment or grinding required.
- STARTING** ● Convenient automatic rewind starter.
- BEARINGS** ● Anti-friction bearings throughout. Needle bearings on crankpin and wrist pin. Needle and ball bearing mains.
- CYLINDER** ● Cast aluminum alloy for maximum heat dissipation. Chrome plated bore for maximum life.
- SPARK TIMING** ● 30° BTDC static.

GENERAL

- SPARK PLUG** ● Champion CJ-6 (.025 inch gap).
- HANDLE BAR** ● Vinyl coated aluminum tubing, forward mounted for correct balance.
- DIMENSIONS** ● Length 30", Width 12", Height 14.5".
- WEIGHT** ● 24 pounds (without wheel or blade).
- TOOLS** ● Combination wrench and belt tensioning tools included.



HOMELITE XL-88 HEAVY DUTY CARRYING CASE.

Convenient Case To Hold Unit Plus Following Accessories:

One gallon safety gasoline can.

Six-pack 1/2 pint Homelite Engine Oil.

One pair safety goggles.

One spare Polyflex drive belt.

One spare air filter.

One 12" carbide-tipped blade.

One 12" steel cutting wheel.

One 12" concrete cutting wheel.

*Registered trademark of Gates Rubber Company

HOMELITE

A **textron**

DIVISION

PORT CHESTER, N.Y. U.S.A.